

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 1 1
光源	L L D 5 0 2 0 L C C 1 × 1 1 0 8 5 . 0 l m
管理番号	K 0 1 9 0 4 5 7 (0) D R 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		9 7 %																				
保守率		良 中 否	0 . 6	7 7	7 0	6 5	6 2	7 6	7 0	6 5	6 2	7 5	6 9	6 4	6 2	7 3	6 8	6 4	6 1	6 0		
			0 . 8	8 4	7 7	7 3	6 9	8 3	7 7	7 2	6 9	8 1	7 5	7 1	6 8	7 9	7 4	7 1	6 8	6 6		
			1 . 0	8 8	8 2	7 7	7 4	8 7	8 1	7 7	7 4	8 5	8 0	7 6	7 3	8 2	7 8	7 5	7 3	7 1		
			0 . 5 6	1 . 2 5	9 2	8 6	8 2	7 9	9 0	8 5	8 1	7 8	8 8	8 4	8 0	7 8	8 6	8 2	7 9	7 7	7 5	
下方投影面積		c m ²	1 . 5	9 4	8 9	8 5	8 2	9 3	8 8	8 5	8 2	9 0	8 6	8 3	8 1	8 8	8 5	8 2	8 0	7 8		
			等価発光面積	c m ²	2 . 0	9 7	9 3	9 0	8 7	9 6	9 2	8 9	8 6	9 3	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 2
取付 高さ	器具間隔最大限		2 . 5	9 9	9 6	9 3	9 0	9 8	9 5	9 2	9 0	9 5	9 2	9 0	8 8	9 3	9 0	8 8	8 7	8 4		
	横方向 (A)		縦方向 (B)		3 . 0	1 0 1	9 8	9 5	9 3	9 9	9 6	9 4	9 2	9 6	9 4	9 2	9 0	9 4	9 2	9 0	8 9	8 6
H m	0 . 4 1 H m		0 . 4 1 H m		4 . 0	1 0 2	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 8	9 6	9 5	9 3	9 5	9 4	9 3	9 1	8 8
					5 . 0	1 0 3	1 0 1	1 0 0	9 8	1 0 2	1 0 0	9 8	9 7	9 9	9 8	9 6	9 5	9 6	9 5	9 4	9 3	9 0
					7 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	9 9	1 0 0	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2
					1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 3	1 0 4	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 8	9 8	9 7	9 7	9 3

