

屋内照明器具特性	
品番 (品名)	XLGB81836
光源	LED3500_70_455 ×1 455.0 lm
管理番号	K0169185 (0) DR 1
BZ分類	BZ4

器具効率		100 % 上方光束 99 % 下方光束 1 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	43	33	26	22	37	28	23	19	25	20	16	13	14	11	9	8	0				
			0.63	0.8	51	41	34	29	43	35	30	25	30	24	21	18	17	14	12	11	0				
			0.56	1.0	56	47	41	35	48	41	35	31	33	28	25	22	19	16	15	13	0				
				1.25	62	53	47	42	53	46	40	36	36	32	28	26	21	18	17	15	0				
下方投影面積 等価発光面積		cm ²		1.5	65	57	51	47	56	50	45	41	38	34	31	29	22	20	18	17	0				
				2.0	70	64	58	54	60	55	51	47	41	38	35	33	24	22	21	20	0				
取付 高さ	器具間隔最大限		2.5	73	68	63	59	63	58	55	51	43	41	38	36	25	24	23	21	0					
	横方向 (A) 縦方向 (B)																								
H m	1.18 H m	1.35 H m	4.0	78	74	71	68	67	64	61	59	47	45	43	41	27	26	25	24	0					
			5.0	80	77	74	71	69	66	64	62	48	46	45	43	28	27	26	26	0					
			7.0	82	79	77	75	70	69	67	65	49	48	47	46	29	28	28	27	0					
			10.0	83	81	80	78	72	70	69	68	50	49	48	48	29	29	29	28	0					

