

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 5 1
光源	LED2700_70_320 x1 320.0 l m
管理番号	K0150113 (0) DB 1
B Z 分類	BZ4/0.7/BZ3/6.0/BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		9 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		91 %																						
保守率		良 中 否	0.67	0.6	60	49	41	37	58	48	41	36	55	46	40	36	52	44	39	35	33			
			0.63	0.8	70	60	53	48	68	59	53	48	65	57	51	47	62	55	50	46	43			
			0.56	1.0	77	68	61	56	75	67	61	56	71	64	59	55	68	62	57	54	51			
				1.25	83	74	68	64	80	73	67	63	76	70	65	62	73	68	64	60	57			
下方投影面積		cm ²	1.5	86	79	73	69	84	77	72	68	80	74	70	66	76	72	68	65	61				
等価発光面積		cm ²	2.0	91	85	80	76	89	83	79	75	85	80	76	73	81	77	74	71	67				
取付 高さ	器具間隔最大限		2.5	94	89	84	81	92	87	83	80	87	83	80	77	83	80	77	75	71				
	横方向 (A)		縦方向 (B)		3.0	96	91	87	84	94	89	86	83	89	86	83	80	85	83	80	78	74		
H m	1.27 H m	1.27 H m	4.0	98	95	92	89	96	93	90	87	92	89	87	84	88	86	84	82	77				
			5.0	100	97	94	92	98	95	92	90	93	91	89	87	89	87	86	84	79				
			7.0	102	99	97	95	99	97	95	94	95	93	92	90	91	90	88	87	82				
			10.0	103	101	100	98	101	99	98	96	96	95	94	93	92	91	90	89	84				

