

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 5 5
光源	LED2700_70_300 ×1 300.0 l m
管理番号	K0150708 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3 / 4.5 / BZ4

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		7 %	室指数	照明率 (X0.01)																				Z C M	
下方光束		93 %																							
保守率		良 中 否	0.67	0.6	60	49	42	38	59	49	42	37	56	47	41	37	53	46	40	36	34				
			0.63	0.8	71	61	54	49	69	60	54	49	66	58	53	48	63	56	51	48	45				
			1.0	78	69	62	58	76	68	62	57	73	66	60	56	69	63	59	55	52					
			0.56	1.25	83	75	69	65	81	74	69	64	78	72	67	63	74	69	65	62	59				
下方投影面積		c m ²	1.5	87	80	74	70	85	78	73	69	81	76	71	68	78	73	69	66	63					
			2.0	92	86	81	77	90	84	80	76	86	81	77	74	82	78	75	72	69					
等価発光面積		c m ²	2.5	94	89	85	81	92	88	84	80	88	85	81	78	85	82	79	76	73					
			3.0	96	92	88	85	94	90	87	84	90	87	84	81	87	84	81	79	75					
H m	1.24 H m	1.24 H m	4.0	99	95	92	89	97	93	91	88	93	90	88	85	89	87	85	83	79					
			5.0	100	97	95	92	98	95	93	91	94	92	90	88	91	89	87	85	81					
			7.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	90	88	84					
			10.0	103	102	100	99	101	100	98	97	97	96	95	94	94	93	92	91	86					

