

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 7 6
光源	LED3500_70_372 x1 372.0 lm
管理番号	K0147053 (0) DB 1
BZ分類	BZ4/2.3/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		6 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		9 4 %																					
保守率		良 中 否	0 . 6 7	0 . 6	5 8	4 7	3 9	3 4	5 7	4 6	3 9	3 4	5 4	4 4	3 8	3 3	5 1	4 3	3 7	3 3	3 1		
			0 . 6 3	0 . 8	6 8	5 7	4 9	4 4	6 6	5 6	4 9	4 3	6 3	5 4	4 7	4 3	6 0	5 2	4 6	4 2	4 0		
			0 . 5 6	1 . 0	7 4	6 4	5 6	5 1	7 2	6 2	5 6	5 0	6 8	6 0	5 4	4 9	6 5	5 8	5 3	4 9	4 6		
				1 . 2 5	7 9	7 0	6 3	5 8	7 7	6 9	6 2	5 7	7 4	6 6	6 1	5 6	7 0	6 4	5 9	5 5	5 2		
下方投影面積		cm ²	1 . 5	8 3	7 5	6 8	6 3	8 1	7 4	6 7	6 2	7 7	7 1	6 6	6 1	7 4	6 8	6 4	6 0	5 7			
等価発光面積		cm ²	2 . 0	8 9	8 2	7 6	7 1	8 7	8 0	7 5	7 0	8 3	7 7	7 2	6 9	7 9	7 4	7 0	6 7	6 4			
取付 高さ	器具間隔最大限		2 . 5	9 2	8 6	8 1	7 6	9 0	8 4	7 9	7 5	8 6	8 1	7 7	7 4	8 2	7 8	7 5	7 2	6 8			
	横方向 (A)		縦方向 (B)	3 . 0	9 4	8 9	8 4	8 0	9 2	8 7	8 3	7 9	8 8	8 4	8 0	7 7	8 5	8 1	7 8	7 5	7 2		
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	9 7	9 3	8 9	8 6	9 5	9 1	8 8	8 4	9 1	8 8	8 5	8 2	8 8	8 5	8 2	8 0	7 6			
			5 . 0	9 9	9 5	9 2	8 9	9 7	9 4	9 1	8 8	9 3	9 0	8 8	8 6	9 0	8 7	8 5	8 3	7 9			
			7 . 0	1 0 1	9 8	9 6	9 4	9 9	9 7	9 4	9 2	9 5	9 3	9 1	9 0	9 2	9 0	8 8	8 7	8 3			
			1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 1	9 9	9 7	9 6	9 7	9 6	9 4	9 3	9 4	9 2	9 1	9 0	8 6			

