

屋内照明器具特性	
品番 (品名)	NY Y 2 3 0 9 4 K
光源	LED 4 0 0 0 _ 8 5 _ 1 6 7 0 × 1 1 6 7 0 . 0 l m
管理番号	K 0 1 6 4 6 4 5 (0) D B 1
B Z 分類	B Z 5 / 1 . 1 / B Z 4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1)															
保守率		良 中 否	0 . 7 7	0 . 6	5 7	4 5	3 8	3 2	5 6	4 5	3 7	3 2	5 4	4 4	3 7	3 2	5 2	4 3	3 6	3 2	3 0	
			0 . 7 2	0 . 8	6 8	5 6	4 8	4 3	6 6	5 6	4 8	4 3	6 3	5 4	4 7	4 3	6 1	5 3	4 7	4 2	4 0	
			0 . 6 8	1 . 0	7 4	6 4	5 6	5 1	7 3	6 3	5 6	5 0	7 0	6 1	5 5	5 0	6 7	6 0	5 4	5 0	4 8	
				1 . 2 5	8 0	7 1	6 4	5 8	7 9	7 0	6 3	5 8	7 6	6 8	6 2	5 7	7 3	6 6	6 1	5 7	5 5	
下方投影面積		c m ²	1 . 5	8 4	7 6	6 9	6 4	8 3	7 5	6 9	6 4	8 0	7 3	6 7	6 3	7 7	7 1	6 6	6 2	6 0		
			等価発光面積	2 . 0	9 0	8 3	7 7	7 2	8 8	8 2	7 6	7 2	8 5	8 0	7 5	7 1	8 3	7 8	7 4	7 0	6 8	
取付 高さ	器具間隔最大限		2 . 5	9 4	8 7	8 2	7 8	9 2	8 6	8 2	7 7	8 9	8 4	8 0	7 7	8 6	8 2	7 9	7 6	7 3		
	横方向 (A) 縦方向 (B)		3 . 0	9 6	9 1	8 6	8 2	9 4	9 0	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 5	8 2	7 9	7 7		
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	9 9	9 5	9 1	8 8	9 8	9 4	9 0	8 7	9 5	9 1	8 9	8 6	9 2	8 9	8 7	8 5	8 2		
			5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	8 9	9 4	9 2	9 0	8 8	8 5		
			7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9		
			1 0 . 0	1 0 5	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2		

