

屋内照明器具特性	
品番 (品名)	N N F W2 1 0 0 1 J
光源	LDL20S. N/ 11/ 12- K(960) ×1 960. 0 l m
管理番号	K0140078 (3) DR 1
B Z 分類	B Z 6

器具効率		99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.83	0.6	50	37	29	23	47	36	28	23	43	33	26	22	39	30	25	20	17
			0.81	0.8	59	46	38	32	56	45	37	31	50	41	34	29	46	38	32	28	23
			0.77	1.0	65	53	45	38	62	51	43	37	56	47	40	35	50	43	37	33	28
				1.25	70	60	51	45	67	57	50	44	61	53	46	41	55	48	43	39	33
下方投影面積		cm ²		1.5	74	64	57	50	71	62	55	49	64	57	51	46	58	52	47	43	37
			等価発光面積	cm ²	2.0	80	71	64	58	76	68	62	57	70	63	58	53	63	58	53	50
取付高さ	器具間隔最大限			2.5	84	76	70	64	80	73	67	62	73	67	62	58	67	62	58	54	47
	横方向 (A) 縦方向 (B)			3.0	86	79	74	68	83	76	71	66	76	70	66	62	69	65	61	58	51
1.5m	2.14 m	1.9 m		4.0	90	84	79	75	86	81	76	72	79	75	71	67	72	69	66	63	55
2	2.85	2.51		5.0	92	87	83	79	88	84	80	76	81	78	74	71	74	72	69	66	59
2.5	3.56	3.11		7.0	94	91	87	84	91	87	84	81	84	81	78	76	77	75	73	71	63
3	4.29	3.72		10.0	97	94	91	88	93	90	88	86	86	84	82	80	79	78	76	74	66

