

屋内照明器具特性	
品番 (品名)	N N F W2 2 0 0 1 J
光源	LDL20S. N/ 11/ 12- K(960) ×2 960.0 l m
管理番号	K0140080 (1) DR 1
B Z 分類	B Z 6

器具効率		99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.83	0.6	50	38	30	24	48	37	29	24	44	34	28	23	40	32	26	22	19
			0.81	0.8	60	47	39	33	57	46	38	32	52	43	36	31	48	40	34	30	26
			0.77	1.0	66	54	46	40	63	52	45	39	58	49	42	37	53	45	40	35	31
				1.25	72	61	53	47	69	59	51	46	63	55	48	43	58	51	46	41	36
下方投影面積		c m ²		1.5	76	66	58	52	73	64	56	51	67	59	53	48	61	55	50	46	41
			等価発光面積	c m ²	2.0	81	73	66	60	78	70	64	59	72	66	60	56	66	61	57	53
取付 高さ	器具間隔最大限		2.5	85	78	71	66	82	75	69	64	76	70	65	61	70	65	61	58	52	
	横方向 (A)	縦方向 (B)	3.0	88	81	75	70	84	78	73	69	78	73	69	65	72	68	65	61	55	
1.5m	2.17 m	1.92 m	4.0	91	86	81	77	88	83	79	75	82	78	74	71	76	73	70	67	60	
2	2.88	2.52	5.0	93	89	85	81	90	86	82	79	84	80	77	74	78	75	73	70	64	
2.5	3.57	3.13	7.0	96	92	89	86	93	90	87	84	87	84	82	79	81	79	77	75	68	
3	4.34	3.74	10.0	98	95	93	91	95	92	90	88	89	87	85	83	83	81	80	79	71	

