

屋内照明器具特性	
品番 (品名)	N N F W2 2 0 2 0 J
光源	LDL20S. N/ 11/ 12 (960) ×2 960.0 l m
管理番号	K0125168 (3) DR 1
B Z 分類	BZ6/ 0.7/ BZ5/ 0.9/ BZ6

器具効率			97 %		反射率	天井	80 %				70 %				50 %				30 %				0 %				
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
						床	10 %				10 %				10 %				10 %				0 %				
上方光束			13 %		室指数	照明率 (X0.01)																			Z	C	M
下方光束			84 %																								
保守率			良 中 否	0.83	0.6	51	39	31	26	49	38	30	25	45	36	29	25	42	34	28	24	21					
				0.81	0.8	60	48	40	35	58	47	40	34	54	44	38	33	50	42	36	32	29					
				0.77	1.0	66	55	47	41	64	53	46	40	59	50	44	39	55	48	42	38	34					
					1.25	72	61	54	48	69	60	52	47	64	56	50	45	60	53	48	43	39					
下方投影面積			cm ²		1.5	76	66	59	53	73	64	57	52	68	61	55	50	63	57	52	48	44					
等価発光面積			cm ²		2.0	81	73	66	61	78	71	65	59	73	67	62	57	68	63	59	55	50					
取付 高さ	器具間隔最大限				2.5	85	77	71	66	82	75	70	65	76	71	66	62	71	67	63	60	55					
	横方向 (A)		縦方向 (B)		3.0	87	81	75	70	84	78	73	69	79	74	70	66	74	70	66	63	58					
1.5m	2.05 m	1.86 m		4.0	90	85	80	76	87	83	78	75	82	78	75	71	77	74	71	68	63						
2	2.72	2.44		5.0	92	88	84	80	90	86	82	78	84	81	78	75	79	77	74	72	66						
2.5	3.4	3.02		7.0	95	91	88	85	92	89	86	83	87	84	82	80	82	80	78	76	70						
3	4.09	3.6		10.0	97	94	92	89	94	92	89	87	89	87	85	83	84	82	81	79	73						

