

| 屋内照明器具特性 |                                                 |
|----------|-------------------------------------------------|
| 品番 (品名)  | N N F W2 1 0 7 1 K                              |
| 光源       | LDL20S. N/ 11/ 12 (960) ×1 960.0 l m            |
| 管理番号     | K0125148 ( 0 ) DR 1                             |
| B Z 分類   | BZ6/ 0.7/ BZ5/ 3.5/ BZ6/ 4.5/ BZ5<br>/ 6.0/ BZ6 |

| 器具効率     |                     | 97 %             | 反射率              | 天井                  | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|----------|---------------------|------------------|------------------|---------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|
|          |                     |                  |                  | 壁                   | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|          |                     |                  |                  | 床                   | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束     |                     | 12 %             | 室指数              | 照明率 ( X0.01 ) Z C M |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |
| 下方光束     |                     | 85 %             |                  |                     |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |
| 保守率      |                     | 良<br>中<br>否      | 0.83             | 0.6                 | 51   | 39 | 31 | 26 | 49   | 38 | 31 | 26 | 46   | 36 | 30 | 25 | 43   | 34 | 28 | 24 | 21  |  |
|          |                     |                  | 0.81             | 0.8                 | 60   | 49 | 41 | 35 | 58   | 47 | 40 | 34 | 54   | 45 | 38 | 33 | 50   | 43 | 37 | 32 | 29  |  |
|          |                     |                  | 0.77             | 1.0                 | 67   | 55 | 48 | 42 | 64   | 54 | 47 | 41 | 60   | 51 | 45 | 40 | 56   | 48 | 43 | 38 | 35  |  |
|          |                     |                  |                  | 1.25                | 72   | 62 | 54 | 48 | 70   | 60 | 53 | 48 | 65   | 57 | 51 | 46 | 61   | 54 | 49 | 44 | 41  |  |
| 下方投影面積   |                     | c m <sup>2</sup> | 1.5              | 76                  | 67   | 59 | 54 | 74 | 65   | 58 | 53 | 69 | 61   | 56 | 51 | 64 | 58   | 53 | 49 | 45 |     |  |
| 等価発光面積   |                     |                  | c m <sup>2</sup> | 2.0                 | 82   | 74 | 67 | 62 | 79   | 72 | 65 | 60 | 74   | 68 | 63 | 58 | 69   | 64 | 60 | 56 | 51  |  |
| 取付<br>高さ | 器具間隔最大限             |                  | 2.5              | 85                  | 78   | 72 | 67 | 82 | 76   | 71 | 66 | 77 | 72   | 67 | 63 | 73 | 68   | 64 | 61 | 56 |     |  |
|          | 横方向 ( A ) 縦方向 ( B ) |                  | 3.0              | 88                  | 81   | 76 | 71 | 85 | 79   | 74 | 70 | 80 | 75   | 71 | 67 | 75 | 71   | 68 | 64 | 59 |     |  |
| 1.5m     | 2.08 m              | 1.87 m           | 4.0              | 91                  | 86   | 81 | 77 | 88 | 83   | 79 | 76 | 83 | 79   | 76 | 73 | 78 | 75   | 72 | 70 | 64 |     |  |
| 2        | 2.77                | 2.45             | 5.0              | 93                  | 89   | 85 | 81 | 90 | 86   | 83 | 79 | 85 | 82   | 79 | 76 | 80 | 78   | 75 | 73 | 67 |     |  |
| 2.5      | 3.46                | 3.04             | 7.0              | 95                  | 92   | 89 | 86 | 93 | 90   | 87 | 84 | 88 | 85   | 83 | 81 | 83 | 81   | 79 | 77 | 71 |     |  |
| 3        | 4.16                | 3.63             | 10.0             | 97                  | 95   | 92 | 90 | 95 | 92   | 90 | 88 | 90 | 88   | 86 | 84 | 85 | 83   | 82 | 81 | 75 |     |  |

