

屋内照明器具特性	
品番 (品名)	F Y Y 2 2 1 4 0
光源	LED4000_85_1190 ×1 1190.0 lm
管理番号	K0166071 (0) DB 1
B Z 分類	BZ5 / 3.5 / BZ6 / 4.5 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 0 0 %																				
保守率		良 中 否	0 . 8 3	0 . 6	5 5	4 2	3 4	2 8	5 4	4 2	3 4	2 8	5 1	4 0	3 3	2 8	4 9	3 9	3 3	2 8	2 6	
			0 . 8 1	0 . 8	6 4	5 2	4 4	3 8	6 3	5 1	4 3	3 8	6 0	5 0	4 3	3 7	5 7	4 9	4 2	3 7	3 5	
			0 . 7 7	1 . 0	7 1	5 9	5 1	4 5	6 9	5 8	5 0	4 4	6 6	5 6	4 9	4 4	6 3	5 5	4 9	4 4	4 1	
				1 . 2 5	7 6	6 6	5 8	5 1	7 5	6 5	5 7	5 1	7 1	6 3	5 6	5 1	6 8	6 1	5 5	5 0	4 8	
下方投影面積		c m ²	1 . 5	8 1	7 1	6 3	5 7	7 9	7 0	6 2	5 7	7 5	6 8	6 1	5 6	7 2	6 6	6 0	5 5	5 3		
			等価発光面積	c m ²	2 . 0	8 6	7 8	7 1	6 5	8 4	7 7	7 0	6 5	8 1	7 4	6 9	6 4	7 8	7 2	6 7	6 3	6 0
取付 高さ	器具間隔最大限		2 . 5	9 0	8 3	7 6	7 1	8 8	8 1	7 5	7 0	8 5	7 9	7 4	6 9	8 2	7 7	7 2	6 9	6 6		
	横方向 (A)	縦方向 (B)	3 . 0	9 3	8 6	8 0	7 5	9 1	8 5	7 9	7 5	8 8	8 2	7 8	7 4	8 4	8 0	7 6	7 3	7 0		
1 . 5m	1 . 9 4 m	1 . 7 8 m	4 . 0	9 6	9 1	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 1	7 9	7 6		
2	2 . 3 9	2 . 3 5	5 . 0	9 8	9 4	9 0	8 6	9 7	9 2	8 9	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 5	8 2	7 9		
2 . 5	2 . 9 1	2 . 9 1	7 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 7	8 4		
3	3 . 4 2	3 . 6 7	1 0 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 4	9 3	9 1	8 8		

