

# 屋内照明器具特性

品番 (品名)	S F X 0 1 0	
光源	LDA5 L - G / K40 / BT / W ×1	550.0 lm
管理番号	K0152753 ( 0 ) DB 1	
B Z 分類	BZ10	

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		64 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		28 %	壁	10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	cm <sup>2</sup>		1.25	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	
	等価発光面積		cm <sup>2</sup>	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H <sub>m</sub>	0.00H <sub>m</sub>	0.00H <sub>m</sub>	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0	

