

屋内照明器具特性	
品番 (品名)	F Y Y 2 2 2 2 0
光源	LED3500_85_2360 ×1 2360.0 lm
管理番号	K0166073 (0) DB 1
B Z 分類	BZ5 / 3.5 / BZ6 / 4.5 / BZ5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		0 %	下方光束	100 %	室指数	照明率 (X0.01)																				Z C M
保守率						良	0.83	0.6	55	42	34	28	53	41	34	28	51	40	33	28	49	39	33	28	26	
		中	0.81	0.8	64	52	44	38	63	51	43	37	60	50	43	37	57	48	42	37	35					
		否	0.77	1.0	71	59	51	44	69	58	50	44	66	56	49	44	63	55	49	44	41					
下方投影面積		cm ²		1.25	76	66	58	51	75	65	57	51	71	63	56	51	68	61	55	50	48					
等価発光面積		cm ²		1.5	81	71	63	57	79	70	62	56	75	67	61	56	72	66	60	55	53					
				2.0	86	78	71	65	84	77	70	65	81	74	69	64	78	72	67	63	60					
取付高さ	器具間隔最大限			2.5	90	83	76	71	88	81	75	70	85	79	74	69	82	77	72	69	66					
	横方向 (A)		縦方向 (B)	3.0	93	86	80	75	91	85	79	75	88	82	78	74	85	80	76	73	70					
1.5m	1.93 m	1.8 m		4.0	96	91	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76					
2	2.49	2.42		5.0	98	94	90	86	97	93	89	85	94	90	87	84	91	88	85	82	80					
2.5	3.05	3.01		7.0	101	97	94	91	99	96	93	91	96	94	91	89	94	92	89	87	84					
3	3.62	3.68		10.0	103	101	98	96	102	99	97	95	99	97	95	93	96	95	93	91	88					

