

屋内照明器具特性

品番 (品名)	FYY56012C														
光源	LED5000_85_3065 x1 3065.0 1 m														
管理番号	K0155399(0)D 1														
BZ分類	BZ3/0.9/BZ2/1.8/BZ3														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	9%	室指数																			
下方光束	91%	照明率 (X0.01)																			
保守率	良 中 否	0.77	0.6	64	53	47	42	62	53	46	42	59	51	45	41	57	49	44	41	39	
		0.72	0.8	73	64	58	53	71	63	57	53	68	61	56	52	65	59	54	51	48	
			1.0	79	71	65	60	77	70	64	60	74	67	62	59	71	65	61	58	55	
		0.68	1.25	84	77	71	67	82	76	70	66	79	73	69	65	75	71	67	64	61	
下方投影面積	c m ²	1.5	88	81	76	72	86	80	75	71	82	77	73	69	78	74	71	68	64		
		2.0	92	87	82	79	90	85	81	78	86	82	79	76	83	79	76	74	70		
取付高さ	器具間隔最大限		2.5	95	90	87	83	93	89	85	82	89	86	82	80	85	82	80	78	74	
	横方向 (A)	縦方向 (B)	3.0	97	93	90	86	95	91	88	85	91	88	85	83	87	85	82	80	76	
1.5m	1.78 m	1.85 m	4.0	99	96	93	91	97	94	92	89	93	91	89	87	89	87	86	84	80	
2	2.36	2.3	5.0	101	98	96	94	99	96	94	92	95	93	91	89	91	89	88	86	82	
2.5	2.93	2.77	7.0	102	100	99	97	100	99	97	95	96	95	93	92	92	91	90	89	84	
3	3.5	3.26	10.0	104	102	101	100	101	100	99	98	97	96	95	95	94	93	92	91	86	

