

屋内照明器具特性	
品番 (品名)	LGB81774
光源	LED3500_70_4530 x1 4530.0 lm
管理番号	K0161533(0)DR1
BZ分類	BZ8

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	50%	床	10%				10%				10%				10%				0%				
下方光束	50%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	4.5	3.3	2.5	1.9	4.1	3.0	2.3	1.8	3.4	2.5	1.9	1.5	2.7	2.0	1.6	1.2	0.7			
	中	0.6	0.8	5.3	4.1	3.3	2.7	4.9	3.8	3.1	2.5	4.0	3.2	2.6	2.1	3.2	2.6	2.1	1.7	1.1			
	否	0.56	1.0	5.9	4.8	3.9	3.3	5.4	4.4	3.6	3.1	4.5	3.7	3.1	2.6	3.6	3.0	2.5	2.1	1.3			
			1.25	6.5	5.4	4.6	4.0	5.9	5.0	4.2	3.7	4.9	4.2	3.6	3.1	4.0	3.4	2.9	2.6	1.7			
下方投影面積		cm ²	1.5	6.9	5.9	5.1	4.5	6.3	5.4	4.7	4.1	5.2	4.5	4.0	3.5	4.2	3.7	3.3	2.9	1.9			
等価発光面積		cm ²	2.0	7.5	6.6	5.9	5.3	6.8	6.1	5.4	4.9	5.7	5.1	4.6	4.2	4.6	4.2	3.8	3.4	2.3			
取付高さ	器具間隔最大限		2.5	7.8	7.0	6.4	5.8	7.2	6.5	5.9	5.4	6.0	5.5	5.0	4.6	4.9	4.5	4.1	3.8	2.6			
	横方向 (A)	縦方向 (B)	3.0	8.1	7.4	6.8	6.3	7.4	6.8	6.3	5.8	6.2	5.8	5.3	5.0	5.1	4.8	4.4	4.1	2.8			
1.5m	2.44m	2.16m	4.0	8.4	7.8	7.3	6.9	7.8	7.3	6.8	6.4	6.6	6.2	5.8	5.5	5.4	5.1	4.8	4.6	3.2			
2	3.22	2.71	5.0	8.6	8.2	7.7	7.3	8.0	7.6	7.2	6.8	6.8	6.4	6.1	5.8	5.6	5.3	5.1	4.9	3.4			
2.5	4	3.29	7.0	8.9	8.5	8.2	7.8	8.3	7.9	7.6	7.3	7.0	6.7	6.5	6.2	5.8	5.6	5.4	5.2	3.7			
3	4.79	3.88	10.0	9.1	8.8	8.6	8.3	8.5	8.2	8.0	7.7	7.2	7.0	6.8	6.6	6.0	5.9	5.7	5.6	4.0			

