

屋内照明器具特性

品番 (品名)	LGB81775										
光源	LED2700_70_4250 x1 4250.0 lm										
管理番号	K0161533(0)DR1										
BZ分類	BZ8										

器具効率	100%	天井	80%				70%				50%				30%				0%																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																	
		床	10%				10%				10%				10%				0%																	
上方光束	50%	室指数																	照明率 (X0.01)																	ZCM
下方光束	50%																																			
保守率	良 中 否	0.63	0.6	0.56	0.6	45	33	25	19	41	30	23	18	34	25	19	15	27	20	16	12	7														
		0.6	0.8	53	41	33	27	49	38	31	25	40	32	26	21	32	26	21	17	11																
		1.0	1.0	59	48	39	33	54	44	36	31	45	37	31	26	36	30	25	21	13																
		0.56	1.25	65	54	46	40	59	50	42	37	49	42	36	31	40	34	29	26	17																
下方投影面積	c m ²	1.5	69	59	51	45	63	54	47	41	52	45	40	35	42	37	33	29	19																	
		2.0	75	66	59	53	68	61	54	49	57	51	46	42	46	42	38	34	23																	
取付高さ	器具間隔最大限		2.5	78	70	64	58	72	65	59	54	60	55	50	46	49	45	41	38	26																
	横方向 (A)	縦方向 (B)	3.0	81	74	68	63	74	68	63	58	62	58	53	50	51	48	44	41	28																
1.5m	2.44m	2.16m	4.0	84	78	73	69	78	73	68	64	66	62	58	55	54	51	48	46	32																
2	3.22	2.71	5.0	86	82	77	73	80	76	72	68	68	64	61	58	56	53	51	49	34																
2.5	4	3.29	7.0	89	85	82	78	83	79	76	73	70	67	65	62	58	56	54	52	37																
3	4.79	3.88	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	56	40																

