

屋内照明器具特性

品番 (品名)

NTS72222B+NTS90151

光源

LED3500_85_1505 x1 1505.0 lm

管理番号

K0166619 (1) DJ 1

BZ分類

BZ1

器具効率

101 %

上方光束

0 %

下方光束

101 %

天井
壁
床

80 %

70 %

50 %

30 %

0 %

70

50

30

10

70

50

30

10

70

50

30

10

70

50

30

10

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

10 %

室指数

照明率 (X0.01)

ZCM

保守率

良 0.81

中 0.77

否 0.68

下方投影面積

cm²

等価発光面積

cm²

取付

器具間隔最大限

高さ

横方向 (A)

縦方向 (B)

Hm

0.36Hm

0.36Hm

0.6	85	79	76	73	85	79	75	73	83	78	75	73	82	78	75	73	71
0.8	91	86	82	80	90	86	82	80	89	85	82	79	88	84	81	79	78
1.0	95	90	87	84	94	90	87	84	92	89	86	84	91	88	85	83	82
1.25	98	94	91	88	97	93	90	88	95	92	89	87	94	91	89	87	86
1.5	100	96	93	91	99	95	93	91	97	94	92	90	95	93	91	89	88
2.0	102	99	97	95	101	98	96	94	99	97	95	94	97	96	94	93	91
2.5	104	101	99	97	103	100	98	97	101	99	97	96	99	97	96	95	93
3.0	105	102	101	99	104	102	100	98	101	100	98	97	100	98	97	96	94
4.0	106	104	103	101	105	103	102	101	103	101	100	99	101	100	99	98	96
5.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	100	99	97
7.0	107	106	105	104	106	105	104	104	104	103	103	102	101	101	101	100	98
10.0	108	107	106	106	107	106	105	105	105	104	103	103	102	102	102	101	99

配光曲線

ランプ光束1000lm

— 管軸に垂直 (A)
--- 管軸に平行 (B)

直射水平面照度

ランプ光束1000lm

80 lx X 100

60

40

20

H=1.5

H=2

H=2.5

H=3

H=4

H=5

2

1.8

1.6

1.4

1.2

1.0

0.8

0.6

0.4

0.2

0.1

0.05

0.02

0.01

0.005

0.002

0.001

0.0005

0.0002

0.0001

0.00005

0.00002

0.00001

0.000005

0.000002

0.000001

0.0000005

0.0000002

0.0000001

0.00000005

0.00000002

0.00000001

0.000000005

0.000000002

0.000000001

0.0000000005

0.0000000002

0.0000000001

0.00000000005

0.00000000002

0.00000000001

0.000000000005

0.000000000002

0.000000000001

0.0000000000005

0.0000000000002

0.0000000000001

0.00000000000005

0.00000000000002

0.00000000000001

0.000000000000005

0.000000000000002

0.000000000000001

0.0000000000000005

0.0000000000000002

0.0000000000000001

0.00000000000000005

0.00000000000000002

0.00000000000000001

0.000000000000000005

0.000000000000000002

0.000000000000000001

0.0000000000000000005

0.0000000000000000002

0.0000000000000000001

0.00000000000000000005

0.00000000000000000002

0.00000000000000000001

0.000000000000000000005

0.000000000000000000002

0.000000000000000000001

0.0000000000000000000005

0.0000000000000000000002

0.0000000000000000000001

0.00000000000000000000005

0.00000000000000000000002

0.00000000000000000000001

0.000000000000000000000005

0.000000000000000000000002

0.000000000000000000000001

0.0000000000000000000000005

0.0000000000000000000000002

0.0000000000000000000000001

0.00000000000000000000000005

0.00000000000000000000000002

0.00000000000000000000000001

0.000000000000000000000000005

0.000000000000000000000000002

0.000000000000000000000000001

0.0000000000000000000000000005

0.0000000000000000000000000002

0.0000000000000000000000000001

0.00000000000000000000000000005

0.00000000000000000000000000002

0.00000000000000000000000000001

0.000000000000000000000000000005

0.000000000000000000000000000002

0.000000000000000000000000000001

0.0000000000000000000000000000005

0.0000000000000000000000000000002

0.0000000000000000000000000000001

0.00000000000000000000000000000005

0.00000000000000000000000000000002

0.00000000000000000000000000000001

0.000000000000000000000000000000005

0.000000000000000000000000000000002

0.000000000000000000000000000000001

0.0000000000000000000000000000000005

0.0000000000000000000000000000000002

0.0000000000000000000000000000000001

0.00000000000000000000000000000000005

0.00000000000000000000000000000000002

0.00000000000000000000000000000000001

0.000000000000000000000000000000000005

0.000000000000000000000000000000000002

0.000000000000000000000000000000000001

0.0000000000000000000000000000000000005

0.0000000000000000000000000000000000002

0.0000000000000000000000000000000000001

0.00000000000000000000000000000000000005

0.00000000000000000000000000000000000002