

屋内照明器具特性

品番 (品名)	FYY26300	
光源	LED3500_85_7130 x1	7130.0 lm
管理番号	K0149128(0)DB1	
BZ分類	BZ6/1.1/BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	53	40	31	25	51	39	31	25	49	38	30	25	46	37	30	25	23	
	中	0.77	0.8	63	51	42	36	61	50	42	36	58	48	41	35	56	47	40	35	33	
	否	0.68	1.0	70	58	50	43	68	57	49	43	65	56	48	43	62	54	48	43	40	
			1.25	76	66	58	51	75	65	57	51	71	63	56	51	68	61	55	50	48	
下方投影面積	c m ²		1.5	81	71	64	57	79	70	63	57	76	68	62	57	73	66	60	56	53	
	等価発光面積		c m ²	2.0	87	79	72	67	85	78	71	66	82	75	70	65	79	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	83	77	72	86	80	76	71	83	78	74	70	68	
	横方向 (A)	縦方向 (B)	3.0	94	88	82	78	92	86	81	77	89	84	80	76	86	82	78	75	72	
1.5m	2.61 m	2.09 m	4.0	97	92	88	84	96	91	87	83	92	89	85	82	90	86	83	81	78	
2	3.42	2.64	5.0	99	95	92	88	98	94	91	87	95	92	89	86	92	89	87	85	82	
2.5	4.23	3.21	7.0	102	99	96	93	100	97	95	92	97	95	93	91	95	93	91	89	86	
3	5.05	3.8	10.0	104	101	99	97	102	100	98	96	100	98	96	95	97	96	94	93	90	

