

屋内照明器具特性

品番 (品名)	FYY26230															
光源	LED3000_85_4250 x1 4250.0 1m															
管理番号	K0149129(0)DB1															
BZ分類	BZ6/1.1/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否	0.81	0.6	53	40	31	25	51	39	31	25	49	38	30	25	46	37	30	25	23	
		0.77	0.8	63	51	42	36	62	50	42	36	59	48	41	35	56	47	40	35	33	
		0.68	1.0	70	58	50	43	68	57	49	43	65	56	49	43	62	54	48	43	40	
			1.25	76	66	58	51	75	65	57	51	71	63	56	51	68	61	55	50	48	
下方投影面積	c m ²	1.5	81	71	64	57	79	70	63	57	76	68	62	57	73	66	61	56	53		
		2.0	87	79	72	67	85	78	71	66	82	76	70	65	79	73	69	65	62		
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	83	77	72	86	80	76	71	83	78	74	71	68	
	横方向 (A)	縦方向 (B)	3.0	94	88	82	78	92	86	81	77	89	84	80	76	86	82	78	75	72	
1.5m	2.61m	2.09m	4.0	97	92	88	84	96	91	87	83	93	89	85	82	90	87	84	81	78	
2	3.42	2.64	5.0	99	95	92	88	98	94	91	88	95	92	89	86	92	89	87	85	82	
2.5	4.24	3.21	7.0	102	99	96	93	100	98	95	93	98	95	93	91	95	93	91	89	86	
3	5.05	3.8	10.0	104	102	99	97	102	100	98	97	100	98	96	95	97	96	94	93	90	

