

屋内照明器具特性

品番 (品名)	FYY26409														
光源	LED3500_85_8340 x1 8340.0 lm														
管理番号	K0149131(0)DB1														
BZ分類	BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.81	0.6	51	38	29	23	50	37	29	23	47	36	28	23	45	35	28	23	21	
		0.77	0.8	61	48	39	32	59	47	39	32	56	45	38	32	53	44	37	32	29	
			1.0	67	55	46	39	66	54	46	39	62	52	45	39	59	50	44	38	36	
		0.68	1.25	74	62	53	47	72	61	53	46	68	59	52	46	65	57	51	45	43	
下方投影面積	c m ²	1.5	78	67	59	52	76	66	58	52	73	64	57	51	69	62	56	51	48		
		2.0	84	75	68	61	82	74	67	61	79	71	65	60	75	69	64	59	56		
等価発光面積	c m ²	2.5	88	80	73	68	86	79	73	67	83	76	71	66	80	74	69	65	62		
		3.0	91	84	78	73	89	83	77	72	86	80	75	71	83	78	74	70	67		
取付高さ	器具間隔最大限		4.0	95	89	84	80	93	88	83	79	90	85	81	78	87	83	80	76	73	
	横方向 (A)	縦方向 (B)	5.0	98	93	88	84	96	91	87	84	93	89	85	82	90	86	83	81	78	
1.5m	2.31m	2.31m	7.0	100	97	93	90	99	95	92	89	96	93	90	88	93	90	88	86	83	
2	3.03	3.04	10.0	103	100	97	95	101	99	96	94	98	96	94	92	96	94	92	91	87	
2.5	3.73	3.75																			
3	4.49	4.48																			

