

屋内照明器具特性	
品番 (品名)	XNW1030WL
光源	LED3000_85_730 ×1 730.0lm
管理番号	K0167854 (0) DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		100 %																							
保守率		良	0.83	0.6	76	69	64	61	76	68	64	60	74	68	63	60	73	67	63	60	59				
		中	0.81	0.8	84	77	73	69	83	77	72	69	81	76	72	69	80	75	71	69	67				
		否	0.77	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	73				
				1.25	93	87	83	80	92	87	83	80	90	85	82	79	88	84	81	79	77				
下方投影面積		c m ²	1.5	95	91	87	84	94	90	86	84	92	88	85	83	90	87	84	82	81					
等価発光面積			c m ²	2.0	99	95	92	89	97	94	91	89	95	92	90	88	93	91	89	87	85				
取付高さ	器具間隔最大限			2.5	100	97	95	92	99	96	94	92	97	95	93	91	95	93	91	90	88				
	横方向 (A)		縦方向 (B)	3.0	102	99	97	95	101	98	96	94	98	96	94	93	96	95	93	92	90				
H m	0.71 H m		0.71 H m	4.0	103	101	99	98	102	100	98	97	100	98	97	96	98	97	95	94	92				
				5.0	104	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96	93				
				7.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	98	95				
				10.0	106	105	104	104	105	104	103	103	103	102	101	101	101	100	100	99	96				

