

屋内照明器具特性	
品番 (品名)	L G W 8 0 4 2 6
光源	LED5000_70_475 x1 475.0 l m
管理番号	K0160289(0)DR1
BZ分類	BZ10

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	50 %	室指数																			照明率 (X0.01)																			Z C M																		
下方光束	50 %																																																									
保守率	良 中 否	0.63	0.6	0.56	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	4																																				
		0.6	0.8	51	38	29	23	46	35	27	21	37	28	22	17	29	22	17	13	6																																						
		1.0	1.0	57	44	35	29	51	40	32	26	42	33	27	21	33	26	21	17	9																																						
		0.56	1.25	62	50	42	35	56	46	38	32	46	38	31	26	36	30	25	21	11																																						
下方投影面積	c m ²	1.5	66	55	47	40	60	51	43	37	49	42	35	30	39	33	28	24	14																																							
		2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	34	30	18																																							
取付高さ	器具間隔最大限		2.5	76	67	60	54	70	62	55	50	57	51	46	42	46	41	37	34	21																																						
	横方向 (A)	縦方向 (B)	3.0	79	71	64	58	72	65	59	54	60	54	50	45	48	44	40	37	24																																						
H m	0.00 H m	0.00 H m	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	45	42	28																																						
			5.0	85	79	74	69	78	73	69	64	65	61	58	54	53	50	48	45	30																																						
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34																																						
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	59	57	55	53	37																																						

