

屋内照明器具特性	
品番 (品名)	XLX183UEW
光源	LED4000_85_7580 ×1 7580.0 lm
管理番号	K0154865 (8) D 1
BZ分類	BZ5 / 0.9 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %							
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %			
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1)																				Z C M				
保守率		良 中 否	0 . 8 1	0 . 6	5 7	4 5	3 8	3 2	5 6	4 5	3 7	3 2	5 4	4 4	3 7	3 2	5 2	4 3	3 6	3 2	3 0							
			0 . 7 7	0 . 8	6 8	5 6	4 9	4 3	6 6	5 6	4 8	4 3	6 4	5 4	4 8	4 3	6 1	5 3	4 7	4 2	4 0							
			0 . 6 8	1 . 0	7 4	6 4	5 7	5 1	7 3	6 3	5 6	5 1	7 0	6 2	5 5	5 0	6 7	6 0	5 5	5 0	4 8							
				1 . 2 5	8 1	7 1	6 4	5 9	7 9	7 0	6 4	5 8	7 6	6 9	6 3	5 8	7 3	6 7	6 2	5 8	5 5							
下方投影面積 等価発光面積		c m ²	1 . 5	8 5	7 6	7 0	6 4	8 3	7 5	6 9	6 4	8 0	7 3	6 8	6 4	7 7	7 2	6 7	6 3	6 1								
			2 . 0	9 0	8 3	7 8	7 3	8 9	8 2	7 7	7 3	8 6	8 0	7 6	7 2	8 3	7 8	7 4	7 1	6 9								
取付 高さ	器具間隔最大限		2 . 5	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	8 9	8 5	8 1	7 7	8 7	8 3	7 9	7 6	7 4								
	横方向 (A)	縦方向 (B)	3 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 2	9 2	8 8	8 4	8 1	8 9	8 6	8 3	8 0	7 8								
1 . 5 m	1 . 9 4 m	1 . 9 3 m	4 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 5	8 3								
2	2 . 5 6	2 . 5 6	5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 1	9 7	9 5	9 2	9 0	9 5	9 2	9 0	8 9	8 6								
2 . 5	3 . 1 7	3 . 1 7	7 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 2	9 0								
3	3 . 8 1	3 . 8	1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 6	9 5	9 3								

