

屋内照明器具特性	
品番 (品名)	LGB15318K
光源	LDG11L-G/95/W x1 1370.0 lm
管理番号	K0153869(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	86%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	86%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	4.6	3.5	2.8	2.3	4.5	3.5	2.8	2.3	4.3	3.4	2.8	2.3	4.1	3.3	2.7	2.3	2.1
	中	0.63	0.8	5.5	4.4	3.7	3.2	5.4	4.4	3.7	3.2	5.1	4.2	3.6	3.2	4.9	4.1	3.6	3.1	3.0
	否	0.56	1.0	6.1	5.1	4.4	3.8	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.8	5.4	4.7	4.2	3.8	3.6
			1.25	6.6	5.7	5.0	4.5	6.4	5.6	5.0	4.5	6.2	5.4	4.9	4.4	5.9	5.3	4.8	4.4	4.2
下方投影面積	c m <sup>2</sup>		1.5	7.0	6.1	5.5	5.0	6.8	6.1	5.5	5.0	6.5	5.9	5.4	4.9	6.3	5.7	5.3	4.9	4.7
	等価発光面積		c m <sup>2</sup>	2.0	7.5	6.8	6.2	5.8	7.3	6.7	6.2	5.7	7.1	6.5	6.1	5.7	6.8	6.4	6.0	5.6
取付高さ	器具間隔最大限		2.5	7.8	7.2	6.7	6.3	7.7	7.1	6.7	6.3	7.4	7.0	6.6	6.2	7.2	6.8	6.4	6.1	5.9
	横方向 (A)	縦方向 (B)	3.0	8.1	7.6	7.1	6.7	7.9	7.5	7.0	6.7	7.7	7.3	6.9	6.6	7.4	7.1	6.8	6.5	6.3
H m	1.28 H m	1.28 H m	4.0	8.4	8.0	7.6	7.3	8.2	7.9	7.5	7.2	8.0	7.7	7.4	7.1	7.7	7.5	7.2	7.0	6.8
			5.0	8.5	8.2	7.9	7.6	8.4	8.1	7.8	7.6	8.2	7.9	7.7	7.4	7.9	7.7	7.5	7.3	7.1
			7.0	8.7	8.5	8.3	8.1	8.6	8.4	8.2	8.0	8.4	8.2	8.0	7.9	8.2	8.0	7.9	7.7	7.5
			10.0	8.9	8.7	8.6	8.4	8.8	8.6	8.5	8.3	8.6	8.4	8.3	8.2	8.4	8.2	8.1	8.0	7.8

