

屋内照明器具特性	
品番 (品名)	LGD1010V
光源	LED3500_70_416 ×1 416.0 lm
管理番号	K0161908 (1) DB 1
BZ分類	BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束																									
保守率		良 中 否	0 . 6	6 7	5 7	5 1	4 6	6 6	5 6	5 0	4 6	6 4	5 6	5 0	4 6	6 2	5 5	5 0	4 6	4 4					
			0 . 6 3	7 7	6 8	6 2	5 8	7 6	6 8	6 2	5 8	7 4	6 7	6 2	5 8	7 2	6 6	6 1	5 7	5 6					
			1 . 0	8 4	7 6	7 0	6 6	8 2	7 5	7 0	6 6	8 0	7 4	6 9	6 5	7 8	7 3	6 8	6 5	6 3					
			0 . 5 6	1 . 2 5	8 9	8 2	7 7	7 3	8 7	8 1	7 6	7 3	8 5	8 0	7 5	7 2	8 3	7 8	7 5	7 2	7 0				
下方投影面積		c m ²	1 . 5	9 2	8 6	8 1	7 8	9 1	8 5	8 1	7 7	8 8	8 4	8 0	7 7	8 6	8 2	7 9	7 6	7 4					
等価発光面積			c m ²	2 . 0	9 6	9 1	8 7	8 4	9 5	9 0	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	8 0				
取付高さ	器具間隔最大限			2 . 5	9 9	9 5	9 1	8 8	9 7	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4				
H m		1 . 1 5 H m	縦方向 (B)	3 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6				
H m		1 . 1 5 H m		4 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9				
				5 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1				
				7 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4				
				1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 5				

