

# 屋内照明器具特性

品番 (品名)	S F 2 5 1 W K																		
光源	LDA7L-G-E17/Z60E/S/W/2 ×1 760.0 1m																		
管理番号	K0136746(0)DB1																		
BZ分類	BZ10																		

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	51 %	室指数	照明率 ( X0.01 ) ZCM																			
下方光束	37 %																					
保守率	良 中 否	0.63	0.6	0.56	0.6	3.8	2.7	2.0	1.5	3.4	2.5	1.8	1.4	2.7	2.0	1.5	1.1	2.1	1.5	1.1	0.8	0.3
		0.6	0.8	4.5	3.4	2.7	2.2	4.1	3.1	2.4	2.0	3.2	2.5	2.0	1.6	2.4	1.9	1.5	1.2	0.5		
		0.56	1.0	5.0	4.0	3.2	2.7	4.5	3.6	2.9	2.4	3.6	2.9	2.4	1.9	2.7	2.2	1.8	1.5	0.7		
			1.25	5.5	4.5	3.8	3.2	5.0	4.1	3.4	2.9	3.9	3.3	2.8	2.3	3.0	2.5	2.1	1.8	0.9		
下方投影面積	cm <sup>2</sup>	1.5	5.9	4.9	4.2	3.7	5.3	4.5	3.8	3.3	4.2	3.6	3.1	2.7	3.2	2.8	2.4	2.1	1.1			
		2.0	6.3	5.5	4.9	4.3	5.7	5.0	4.4	4.0	4.6	4.1	3.6	3.2	3.5	3.1	2.8	2.5	1.4			
取付高さ	器具間隔最大限		2.5	6.7	6.0	5.4	4.8	6.0	5.4	4.9	4.4	4.9	4.4	4.0	3.6	3.8	3.4	3.1	1.6			
	横方向 (A)	縦方向 (B)	3.0	6.9	6.3	5.7	5.2	6.3	5.7	5.2	4.8	5.1	4.6	4.2	3.9	3.9	3.6	3.3	1.8			
Hm	0.00Hm	0.00Hm	4.0	7.2	6.7	6.2	5.8	6.6	6.1	5.7	5.3	5.3	5.0	4.6	4.3	4.2	3.9	3.7	2.0			
			5.0	7.4	6.9	6.5	6.1	6.8	6.4	6.0	5.6	5.5	5.2	4.9	4.6	4.3	4.1	3.9	2.2			
			7.0	7.7	7.3	7.0	6.6	7.0	6.7	6.4	6.1	5.7	5.5	5.3	5.0	4.6	4.4	4.2	2.5			
			10.0	7.9	7.6	7.3	7.1	7.2	6.9	6.7	6.5	5.9	5.7	5.6	5.4	4.7	4.6	4.4	2.7			

