

屋内照明器具特性	
品番 (品名)	LGD1030V
光源	LED3500_70_219 ×1 219.0 l m
管理番号	K0161901 (1) DB 1
B Z 分類	BZ1

器具効率	1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束	0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束	1 0 0 %																					
保守率	良 中 否	0 . 6 7	0 . 6	9 6	9 3	9 1	8 9	9 6	9 3	9 1	8 9	9 5	9 2	9 0	8 9	9 4	9 2	9 0	8 9	8 8		
		0 . 6 3	0 . 8	9 9	9 6	9 4	9 2	9 8	9 6	9 4	9 2	9 7	9 5	9 3	9 2	9 6	9 4	9 3	9 2	9 1		
		0 . 5 6	1 . 0	1 0 1	9 8	9 6	9 5	1 0 0	9 8	9 6	9 4	9 9	9 7	9 5	9 4	9 8	9 6	9 5	9 4	9 3		
			1 . 2 5	1 0 2	1 0 0	9 8	9 7	1 0 1	9 9	9 8	9 6	1 0 0	9 8	9 7	9 6	9 9	9 7	9 6	9 5	9 4		
下方投影面積	c m ²	1 . 5	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 8	1 0 1	9 9	9 8	9 7	1 0 0	9 8	9 7	9 6	9 5			
		2 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 1	9 9	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 8	9 6			
等価発光面積	c m ²	2 . 5	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 1	1 0 0	9 9	9 8	9 7			
		3 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 0	9 9	9 7			
H m	0 . 3 7 H m	0 . 3 7 H m	4 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 8			
			5 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	9 8			
			7 . 0	1 0 7	1 0 6	1 0 6	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	9 9			
			1 0 . 0	1 0 7	1 0 7	1 0 7	1 0 6	1 0 6	1 0 6	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	9 9			

