

屋内照明器具特性

品番 (品名)	LGB15370K									
光源	LDG11L-G/95/W x1					1370.0 lm				
管理番号	K0147993(0)DB1									
BZ分類	BZ6/1.1/BZ5									

器具効率	84%	天井	80%				70%				50%				30%				0%				
	上方光束		21%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		63%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.67	0.6	41	31	24	19	39	30	23	19	35	27	22	18	32	25	20	16	13			
	中	0.63	0.8	50	40	33	28	47	38	32	27	42	35	29	25	38	32	27	24	20			
	否	0.56	1.0	55	46	39	34	53	44	38	33	47	40	35	31	43	37	32	29	25			
			0.56	1.25	61	52	46	41	58	50	44	39	52	46	41	37	47	42	38	35	30		
下方投影面積			c m ²																				
			c m ²																				
取付高さ	器具間隔最大限																						
	横方向 (A)	縦方向 (B)																					
H m	1.70 H m	1.70 H m	4.0	78	74	71	68	74	71	68	65	68	66	63	61	63	60	58	57	50			
			5.0	79	76	73	71	76	73	71	68	70	68	66	64	64	62	61	59	52			
			7.0	81	79	77	75	78	76	74	72	72	70	69	67	66	65	64	62	55			
			10.0	83	81	79	78	80	78	77	75	73	72	71	70	68	67	66	65	57			

