

# 屋内照明器具特性

|         |                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB15372K                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LDG11L-G/95/W x1 1370.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0147993(0)DB1             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ6/1.1/BZ5                |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                   |          |                  |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |    |
|--------|-------------------|----------|------------------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|----|
| 器具効率   | 84%               | 天井       | 80%              |      |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |    |
|        | 上方光束              |          | 21%              | 反射率  | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0% |
|        | 下方光束              |          | 63%              |      | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |    |
| 室指数    | 照明率 ( X0.01 ) ZCM |          |                  |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |    |
| 保守率    | 良                 | 0.67     | 0.6              | 41   | 31 | 24  | 19  | 39 | 30 | 23  | 19  | 35 | 27 | 22  | 18  | 32 | 25 | 20  | 16 | 13 |    |
|        | 中                 | 0.63     | 0.8              | 50   | 40 | 33  | 28  | 47 | 38 | 32  | 27  | 42 | 35 | 29  | 25  | 38 | 32 | 27  | 24 | 20 |    |
|        | 否                 | 0.56     | 1.0              | 55   | 46 | 39  | 34  | 53 | 44 | 38  | 33  | 47 | 40 | 35  | 31  | 43 | 37 | 32  | 29 | 25 |    |
|        |                   |          | 1.25             | 61   | 52 | 46  | 41  | 58 | 50 | 44  | 39  | 52 | 46 | 41  | 37  | 47 | 42 | 38  | 35 | 30 |    |
| 下方投影面積 |                   |          | c m <sup>2</sup> | 1.5  | 65 | 57  | 51  | 46 | 61 | 54  | 49  | 44 | 56 | 50  | 45  | 42 | 50 | 46  | 42 | 39 | 34 |
|        | 等価発光面積            |          | c m <sup>2</sup> | 2.0  | 70 | 63  | 58  | 53 | 66 | 61  | 56  | 52 | 60 | 56  | 52  | 48 | 55 | 51  | 48 | 45 | 39 |
| 取付高さ   | 器具間隔最大限           |          |                  | 2.5  | 73 | 67  | 63  | 59 | 70 | 65  | 60  | 57 | 64 | 60  | 56  | 53 | 58 | 55  | 52 | 49 | 43 |
|        | 横方向 (A)           | 縦方向 (B)  |                  | 3.0  | 75 | 70  | 66  | 62 | 72 | 67  | 64  | 60 | 66 | 62  | 59  | 56 | 60 | 57  | 55 | 53 | 46 |
| H m    | 1.70 H m          | 1.70 H m |                  | 4.0  | 78 | 74  | 71  | 68 | 74 | 71  | 68  | 65 | 68 | 66  | 63  | 61 | 63 | 60  | 58 | 57 | 50 |
|        |                   |          |                  | 5.0  | 79 | 76  | 73  | 71 | 76 | 73  | 71  | 68 | 70 | 68  | 66  | 64 | 64 | 62  | 61 | 59 | 52 |
|        |                   |          |                  | 7.0  | 81 | 79  | 77  | 75 | 78 | 76  | 74  | 72 | 72 | 70  | 69  | 67 | 66 | 65  | 64 | 62 | 55 |
|        |                   |          |                  | 10.0 | 83 | 81  | 79  | 78 | 80 | 78  | 77  | 75 | 73 | 72  | 71  | 70 | 68 | 67  | 66 | 65 | 57 |

