

屋内照明器具特性

品番 (品名)	LSEB3114K																
光源	LDG11L-G/95/W x1 1370.0 lm																
管理番号	K0147992(0)DB1																
BZ分類	BZ6																

器具効率	56%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	2%	室指数	照明率 (X0.01) ZCM																		
下方光束	54%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	2.9	2.1	1.7	1.3	2.8	2.1	1.6	1.3	2.6	2.0	1.6	1.3	2.5	1.9	1.6	1.3	1.2		
		0.8	3.4	2.7	2.2	1.9	3.3	2.7	2.2	1.9	3.1	2.6	2.1	1.8	3.0	2.5	2.1	1.8	1.7		
		1.0	3.8	3.1	2.6	2.3	3.7	3.1	2.6	2.2	3.5	2.9	2.5	2.2	3.3	2.8	2.5	2.2	2.0		
		1.25	4.1	3.5	3.0	2.7	4.0	3.4	3.0	2.6	3.8	3.3	2.9	2.6	3.6	3.2	2.8	2.6	2.4		
下方投影面積	c m ²	1.5	4.4	3.8	3.3	3.0	4.3	3.7	3.3	3.0	4.0	3.6	3.2	2.9	3.8	3.4	3.1	2.9	2.7		
		2.0	4.7	4.2	3.8	3.5	4.6	4.1	3.8	3.4	4.4	4.0	3.6	3.4	4.2	3.8	3.5	3.3	3.1		
取付高さ	器具間隔最大限		2.5	4.9	4.5	4.1	3.8	4.8	4.4	4.1	3.8	4.6	4.2	3.9	3.7	4.4	4.1	3.8	3.6	3.4	
	横方向 (A)	縦方向 (B)	3.0	5.1	4.7	4.4	4.1	5.0	4.6	4.3	4.0	4.7	4.4	4.2	3.9	4.5	4.3	4.0	3.8	3.6	
H m	1.47 H m	1.47 H m	4.0	5.3	5.0	4.7	4.4	5.2	4.9	4.6	4.4	5.0	4.7	4.5	4.3	4.8	4.5	4.3	4.2	4.0	
			5.0	5.4	5.1	4.9	4.6	5.3	5.0	4.8	4.6	5.1	4.9	4.7	4.5	4.9	4.7	4.5	4.4	4.2	
			7.0	5.6	5.3	5.1	5.0	5.5	5.3	5.1	4.9	5.3	5.1	4.9	4.8	5.1	4.9	4.8	4.7	4.4	
			10.0	5.7	5.5	5.4	5.2	5.6	5.4	5.3	5.1	5.4	5.3	5.1	5.0	5.2	5.1	5.0	4.9	4.7	

