

屋内照明器具特性

品番 (品名)	LGB73501															
光源	LED3500_70_450 x1 450.0 l m															
管理番号	K0151698(0)D 1															
BZ分類	BZ3															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	64	54	47	42	63	53	47	42	61	52	47	42	59	51	46	42	40
	中	0.63	0.8	74	65	58	54	73	64	58	54	71	63	58	53	69	62	57	53	51
	否	0.56	1.0	81	72	66	62	80	72	66	61	77	70	65	61	75	69	64	61	59
			1.25	86	79	73	69	85	78	73	68	82	76	72	68	80	75	71	67	66
下方投影面積		cm ²	1.5	90	83	78	74	88	82	77	73	86	81	76	73	83	79	75	72	70
等価発光面積		cm ²	2.0	94	89	84	81	93	88	84	80	90	86	83	79	88	84	81	79	77
取付高さ	器具間隔最大限		2.5	97	93	89	85	96	92	88	85	93	90	87	84	91	88	85	83	81
	横方向 (A)	縦方向 (B)	3.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	86	83
H _m	1.15H _m	1.15H _m	4.0	101	98	95	93	100	97	95	92	98	95	93	91	95	93	91	90	87
			5.0	103	100	98	96	102	99	97	95	99	97	95	94	97	95	94	92	90
			7.0	104	102	101	99	103	101	100	98	101	99	98	97	98	97	96	95	92
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	94

