

# 屋内照明器具特性

|         |                     |          |
|---------|---------------------|----------|
| 品番 (品名) | LGB73600            |          |
| 光源      | LED5000_70_470 ×1   | 470.0 lm |
| 管理番号    | K0151699(0)D 1      |          |
| BZ分類    | BZ1/3.5/BZ2/8.5/BZ1 |          |

|        |         |                 |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|
| 器具効率   | 100%    | 天井              | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0%  |    |
|        | 上方光束    |                 | 0%          | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 0% |
| 下方光束   | 100%    | 床               | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0%  |    |
| 室指数    |         |                 | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |    |
| 保守率    | 良       | 0.67            | 0.6         | 74  | 65  | 60  | 56  | 73  | 65  | 60  | 56  | 71  | 64  | 59  | 56  | 69  | 63  | 59 | 56  | 54 |
|        | 中       | 0.63            | 0.8         | 81  | 74  | 69  | 65  | 80  | 73  | 68  | 65  | 78  | 72  | 68  | 64  | 77  | 71  | 67 | 64  | 63 |
|        | 否       | 0.56            | 1.0         | 86  | 80  | 75  | 71  | 85  | 79  | 74  | 71  | 83  | 78  | 74  | 70  | 81  | 77  | 73 | 70  | 68 |
| 下方投影面積 | 等価発光面積  | cm <sup>2</sup> | 1.25        | 91  | 85  | 80  | 76  | 90  | 84  | 80  | 76  | 87  | 83  | 79  | 76  | 85  | 81  | 78 | 75  | 74 |
|        |         |                 | 1.5         | 94  | 88  | 84  | 81  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 80  | 88  | 84  | 82 | 79  | 77 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5         | 100 | 96  | 93  | 90  | 98  | 95  | 92  | 89  | 96  | 93  | 91  | 88  | 94  | 91  | 89 | 88  | 85 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0         | 101 | 98  | 95  | 93  | 100 | 97  | 94  | 92  | 97  | 95  | 93  | 91  | 95  | 93  | 91 | 90  | 88 |
| Hm     | 0.50Hm  | 0.50Hm          | 4.0         | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97  | 96  | 94  | 97  | 96  | 94 | 93  | 90 |
|        |         |                 | 5.0         | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 98  | 100 | 99  | 97  | 96  | 98  | 97  | 96 | 95  | 92 |
|        |         |                 | 7.0         | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98 | 97  | 94 |
|        |         |                 | 10.0        | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99 | 99  | 96 |

