

屋内照明器具特性	
品番 (品名)	L G W8 0 3 6 4
光源	LED2700_70_265 ×1 265.0 l m
管理番号	K0171393 (0) DB 1
B Z 分類	BZ6 / 1.4 / BZ5 / 1.8 / BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		4 9 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 8	3 7	2 9	2 4	4 4	3 4	2 7	2 3	3 7	2 9	2 4	2 0	3 0	2 4	2 0	1 7	1 2	
			0 . 6	0 . 8	5 7	4 6	3 8	3 3	5 2	4 2	3 6	3 1	4 4	3 6	3 1	2 7	3 6	3 0	2 6	2 3	1 6	
				1 . 0	6 3	5 2	4 5	3 9	5 8	4 9	4 2	3 7	4 9	4 1	3 6	3 2	4 0	3 5	3 1	2 7	1 9	
			0 . 5 6	1 . 2 5	6 8	5 9	5 2	4 6	6 3	5 5	4 8	4 3	5 3	4 6	4 1	3 7	4 4	3 9	3 5	3 2	2 3	
下方投影面積		c m ²	1 . 5	7 2	6 4	5 7	5 1	6 7	5 9	5 3	4 8	5 6	5 0	4 5	4 2	4 6	4 2	3 8	3 5	2 5		
			2 . 0	7 8	7 0	6 4	5 9	7 2	6 5	6 0	5 5	6 1	5 6	5 1	4 8	5 0	4 6	4 3	4 1	2 9		
取付 高さ	器具間隔最大限		2 . 5	8 1	7 5	6 9	6 4	7 5	6 9	6 4	6 0	6 3	5 9	5 5	5 2	5 3	4 9	4 7	4 4	3 2		
	横方向 (A) 縦方向 (B)		3 . 0	8 4	7 8	7 3	6 9	7 7	7 2	6 8	6 4	6 5	6 2	5 8	5 5	5 4	5 2	4 9	4 7	3 4		
H m	1 . 3 7 H m	1 . 2 9 H m	4 . 0	8 7	8 2	7 8	7 4	8 0	7 6	7 3	6 9	6 8	6 5	6 2	6 0	5 7	5 5	5 2	5 1	3 7		
			5 . 0	8 9	8 5	8 1	7 8	8 2	7 9	7 6	7 3	7 0	6 7	6 5	6 3	5 8	5 6	5 5	5 3	3 9		
			7 . 0	9 1	8 8	8 5	8 3	8 4	8 2	7 9	7 7	7 2	7 0	6 8	6 6	6 0	5 9	5 7	5 6	4 1		
			1 0 . 0	9 3	9 0	8 8	8 6	8 6	8 4	8 2	8 1	7 4	7 2	7 1	6 9	6 2	6 1	6 0	5 9	4 3		

