

屋内照明器具特性	
品番 (品名)	L G D 1 4 0 0 L
光源	LED2700_70_420 ×1 420.0 l m
管理番号	K0151186 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束																								
保守率		良 中 否	0 . 6 7	0 . 6	6 2	5 1	4 4	3 9	6 1	5 0	4 4	3 9	5 9	4 9	4 3	3 9	5 7	4 8	4 3	3 9	3 7			
			0 . 6 3	0 . 8	7 3	6 3	5 6	5 1	7 1	6 2	5 6	5 1	6 9	6 1	5 5	5 1	6 7	6 0	5 4	5 0	4 8			
			0 . 5 6	1 . 0	7 9	7 1	6 4	5 9	7 8	7 0	6 4	5 9	7 6	6 8	6 3	5 9	7 3	6 7	6 2	5 8	5 6			
				1 . 2 5	8 5	7 7	7 1	6 7	8 4	7 7	7 1	6 7	8 1	7 5	7 0	6 6	7 9	7 3	6 9	6 6	6 4			
下方投影面積		c m ²	1 . 5	8 9	8 2	7 7	7 2	8 8	8 1	7 6	7 2	8 5	7 9	7 5	7 1	8 2	7 8	7 4	7 1	6 9				
等価発光面積			c m ²	2 . 0	9 4	8 8	8 4	8 0	9 2	8 7	8 3	7 9	9 0	8 5	8 2	7 8	8 7	8 4	8 0	7 8	7 5			
				2 . 5	9 7	9 2	8 8	8 5	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 5	8 2	8 0			
取付 高さ	器具間隔最大限		3 . 0	9 9	9 5	9 1	8 8	9 7	9 4	9 0	8 7	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 3				
	横方向 (A)		縦方向 (B)		4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7		
H m	1 . 2 3 H m		1 . 2 4 H m		5 . 0	1 0 3	1 0 0	9 8	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9		
					7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2		
					1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4		

