

# 屋内照明器具特性

品番 (品名)	S F 9 6 5 S Z	
光源	LDA4 L - H - E17 / E / S / W / 2 x1	440.0 l m
管理番号	K0123365 ( 0 ) DB 1	
BZ分類	BZ9	

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		75 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	14 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	3.9	2.9	2.2	1.8	3.4	2.5	2.0	1.6	2.4	1.8	1.5	1.2	1.6	1.2	1.0	0.8	1
	中	0.6	0.6	4.6	3.6	2.9	2.5	4.0	3.2	2.6	2.2	2.9	2.3	1.9	1.6	1.9	1.5	1.3	1.1	2
	否	0.56	1.0	5.1	4.2	3.5	3.0	4.4	3.6	3.1	2.7	3.2	2.7	2.3	2.0	2.1	1.8	1.5	1.3	3
			1.25	5.5	4.7	4.1	3.6	4.8	4.1	3.6	3.2	3.5	3.0	2.7	2.4	2.3	2.0	1.8	1.6	4
下方投影面積		cm <sup>2</sup>	1.5	5.9	5.1	4.5	4.0	5.1	4.5	4.0	3.6	3.7	3.3	2.9	2.7	2.5	2.2	2.0	1.8	4
等価発光面積		cm <sup>2</sup>	2.0	6.3	5.7	5.1	4.7	5.5	5.0	4.5	4.1	4.1	3.7	3.4	3.1	2.7	2.5	2.3	2.1	6
取付高さ	器具間隔最大限		2.5	6.6	6.0	5.6	5.1	5.8	5.3	4.9	4.6	4.3	3.9	3.7	3.4	2.9	2.6	2.5	2.3	6
	横方向 (A)	縦方向 (B)	3.0	6.8	6.3	5.9	5.5	6.0	5.6	5.2	4.9	4.4	4.1	3.9	3.7	3.0	2.8	2.6	2.5	7
H	0.00H	0.00H	4.0	7.1	6.7	6.3	6.0	6.2	5.9	5.6	5.3	4.6	4.4	4.2	4.0	3.1	3.0	2.8	2.7	8
			5.0	7.2	6.9	6.6	6.3	6.4	6.1	5.8	5.6	4.8	4.6	4.4	4.2	3.2	3.1	3.0	2.9	9
			7.0	7.4	7.2	6.9	6.7	6.6	6.4	6.2	6.0	4.9	4.8	4.6	4.5	3.3	3.2	3.1	3.1	10
			10.0	7.6	7.4	7.2	7.0	6.7	6.6	6.4	6.3	5.0	4.9	4.8	4.7	3.4	3.4	3.3	3.2	11

