

# 屋内照明器具特性

|         |                  |  |  |  |  |  |  |  |          |  |  |  |  |  |  |  |
|---------|------------------|--|--|--|--|--|--|--|----------|--|--|--|--|--|--|--|
| 品番 (品名) | LGWC85203BK      |  |  |  |  |  |  |  |          |  |  |  |  |  |  |  |
| 光源      | LDA3L-E17/C/W x1 |  |  |  |  |  |  |  | 280.0 lm |  |  |  |  |  |  |  |
| 管理番号    | K0133085(0)DB1   |  |  |  |  |  |  |  |          |  |  |  |  |  |  |  |
| BZ分類    | BZ4/0.7/BZ5      |  |  |  |  |  |  |  |          |  |  |  |  |  |  |  |

|        |                   |         |      |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |    |
|--------|-------------------|---------|------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|----|
| 器具効率   | 86%               | 天井      | 80%  |     |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |    |
|        | 上方光束              |         | 18%  | 反射率 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0% |
|        | 下方光束              |         | 68%  |     | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |    |
| 室指数    | 照明率 ( X0.01 ) ZCM |         |      |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |    |
| 保守率    | 良                 | 0.67    | 0.6  | 48  | 38 | 32  | 27  | 46 | 37 | 31  | 27  | 42 | 34 | 29  | 25  | 39 | 32 | 28  | 24 | 22 |    |
|        | 中                 | 0.63    | 0.8  | 55  | 45 | 39  | 34  | 53 | 44 | 38  | 33  | 48 | 41 | 36  | 32  | 44 | 38 | 34  | 30 | 27 |    |
|        | 否                 | 0.56    | 1.0  | 60  | 51 | 44  | 39  | 57 | 49 | 43  | 38  | 52 | 46 | 40  | 36  | 48 | 42 | 38  | 35 | 31 |    |
|        |                   |         | 1.25 | 65  | 56 | 50  | 45  | 62 | 54 | 48  | 44  | 57 | 50 | 46  | 42  | 52 | 47 | 43  | 39 | 35 |    |
| 下方投影面積 |                   |         | 1.5  | 68  | 60 | 54  | 49  | 65 | 58 | 53  | 48  | 60 | 54 | 49  | 46  | 55 | 50 | 46  | 43 | 38 |    |
|        |                   |         | 2.0  | 73  | 66 | 61  | 56  | 70 | 64 | 59  | 55  | 64 | 59 | 55  | 52  | 59 | 55 | 52  | 49 | 43 |    |
| 取付高さ   | 器具間隔最大限           |         | 2.5  | 76  | 70 | 65  | 61  | 73 | 67 | 63  | 59  | 67 | 63 | 59  | 56  | 61 | 58 | 55  | 52 | 47 |    |
|        | 横方向 (A)           | 縦方向 (B) | 3.0  | 78  | 73 | 68  | 64  | 75 | 70 | 66  | 63  | 69 | 65 | 62  | 59  | 63 | 60 | 58  | 55 | 49 |    |
| Hm     | 1.31Hm            | 1.28Hm  | 4.0  | 80  | 76 | 73  | 69  | 77 | 74 | 70  | 67  | 71 | 68 | 66  | 63  | 66 | 63 | 61  | 59 | 53 |    |
|        |                   |         | 5.0  | 82  | 79 | 75  | 73  | 79 | 76 | 73  | 70  | 73 | 70 | 68  | 66  | 67 | 65 | 64  | 62 | 55 |    |
|        |                   |         | 7.0  | 84  | 81 | 79  | 77  | 81 | 78 | 76  | 74  | 75 | 73 | 71  | 70  | 69 | 68 | 66  | 65 | 58 |    |
|        |                   |         | 10.0 | 85  | 84 | 82  | 80  | 82 | 81 | 79  | 77  | 77 | 75 | 74  | 72  | 71 | 70 | 69  | 68 | 61 |    |

