

屋内照明器具特性	
品番 (品名)	L G D 3 1 0 4
光源	LED2700_70_500 ×1 500.0 l m
管理番号	K0154607 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束				100 %																				
保守率		良 中 否	0.67	0.6	61	50	42	37	60	49	42	37	58	48	42	37	55	47	41	37	35			
			0.63	0.8	72	61	55	49	70	61	54	49	68	60	54	49	66	58	53	49	47			
			0.56	1.0	79	69	63	58	77	69	62	58	75	67	62	57	72	66	61	57	55			
				1.25	85	77	71	66	83	76	70	66	81	74	69	65	78	73	68	65	63			
下方投影面積		cm ²	1.5	89	81	76	71	87	81	75	71	84	79	74	71	82	77	73	70	68				
等価発光面積			cm ²	2.0	94	88	83	79	92	87	83	79	90	85	81	78	87	83	80	77	75			
取付高さ	器具間隔最大限			2.5	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	82	80			
		横方向 (A)		縦方向 (B)		3.0	99	95	91	88	97	93	90	87	95	92	89	86	92	90	87	85	83	
H m	1.26 H m		1.26 H m		4.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	89	87		
					5.0	103	100	98	95	101	99	97	95	99	97	95	93	96	95	93	92	89		
					7.0	104	102	101	99	103	101	100	98	101	99	98	96	98	97	96	95	92		
					10.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	94		

