

屋内照明器具特性	
品番 (品名)	LGB17182
光源	LED2700_70_1119 x1 1119.0 lm
管理番号	K0153989(0)DB1
BZ分類	BZ5/0.7/BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	58	47	39	34	57	46	39	34	55	45	38	33	53	44	38	33	31
	中	0.63	0.8	69	58	50	45	67	57	50	45	65	56	49	44	62	54	49	44	42
	否	0.56	1.0	75	65	58	52	74	64	58	52	71	63	57	52	68	61	56	52	49
			1.25	81	72	65	60	80	71	65	60	77	70	64	59	74	68	63	59	57
下方投影面積	c m ²		1.5	85	77	71	66	84	76	70	65	81	74	69	65	78	73	68	64	62
	等価発光面積		c m ²	2.0	91	84	78	74	89	83	78	73	86	81	76	73	84	79	75	72
取付高さ	器具間隔最大限		2.5	94	88	84	79	93	87	83	79	90	85	81	78	87	83	80	77	75
	横方向 (A)	縦方向 (B)	3.0	97	91	87	83	95	90	86	83	92	88	85	82	90	86	83	81	78
1.5m	1.94 m	2.03 m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	86	83
2	2.58	2.62	5.0	101	98	95	92	100	97	94	92	97	95	92	90	95	92	91	89	86
2.5	3.21	3.22	7.0	103	101	99	96	102	100	98	96	99	97	96	94	97	95	94	92	90
3	3.84	3.83	10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	97	96	95	92

