

屋内照明器具特性

品番 (品名)	L G W 8 5 0 1 6 Z														
光源	LDA4L - H - E17 / E / S / W / 2 × 1 440.0 l m														
管理番号	K0126057 (1) DB 1														
B Z 分類	B Z 6														

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		21 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		64 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0.01) Z C M																				
保守率	良	0.63	0.6	4.2	3.1	2.4	1.9	4.0	3.0	2.3	1.9	3.5	2.7	2.1	1.7	3.2	2.5	2.0	1.6	1.3	
	中	0.6	0.8	4.9	3.9	3.2	2.7	4.7	3.7	3.1	2.6	4.2	3.4	2.8	2.4	3.7	3.1	2.6	2.2	1.8	
	否	0.56	1.0	5.5	4.5	3.7	3.2	5.2	4.3	3.6	3.1	4.6	3.9	3.3	2.9	4.1	3.5	3.0	2.7	2.2	
			1.25	5.9	5.0	4.3	3.8	5.6	4.8	4.1	3.6	5.0	4.4	3.8	3.4	4.5	4.0	3.5	3.1	2.6	
下方投影面積	c m ²		1.5	6.3	5.4	4.7	4.2	6.0	5.2	4.6	4.1	5.4	4.7	4.2	3.8	4.8	4.3	3.8	3.5	3.0	
	等価発光面積		c m ²	2.0	6.8	6.0	5.4	4.9	6.4	5.8	5.2	4.7	5.8	5.2	4.8	4.4	5.2	4.8	4.4	4.0	3.4
取付高さ	器具間隔最大限		2.5	7.1	6.4	5.9	5.4	6.7	6.1	5.6	5.2	6.1	5.6	5.2	4.8	5.5	5.1	4.7	4.4	3.8	
	横方向 (A)	縦方向 (B)	3.0	7.3	6.7	6.2	5.8	7.0	6.4	6.0	5.6	6.3	5.9	5.5	5.1	5.7	5.3	5.0	4.7	4.1	
H m	1.32 H m	1.32 H m	4.0	7.6	7.1	6.7	6.3	7.3	6.8	6.4	6.1	6.6	6.2	5.9	5.6	6.0	5.7	5.4	5.2	4.5	
			5.0	7.8	7.4	7.0	6.6	7.4	7.1	6.7	6.4	6.8	6.5	6.2	5.9	6.2	5.9	5.7	5.5	4.7	
			7.0	8.0	7.7	7.4	7.1	7.7	7.4	7.1	6.8	7.0	6.8	6.5	6.3	6.4	6.2	6.0	5.8	5.1	
			10.0	8.2	8.0	7.7	7.5	7.9	7.6	7.4	7.2	7.2	7.0	6.8	6.7	6.6	6.4	6.3	6.2	5.4	

