

屋内照明器具特性	
品番 (品名)	L G D 3 1 3 6 L
光源	L E D 2 7 0 0 _ 7 0 _ 6 6 0 × 1 6 6 0 . 0 l m
管理番号	K 0 1 5 9 0 2 9 (0) D B 1
B Z 分類	B Z 1

器具効率		1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																			
下方光束		1 0 1 %																					
保守率		良	0 . 6 7	0 . 6	7 7	7 0	6 5	6 2	7 7	6 9	6 5	6 2	7 5	6 9	6 4	6 1	7 4	6 8	6 4	6 1	6 0		
		中	0 . 6 3	0 . 8	8 5	7 8	7 3	7 0	8 4	7 7	7 3	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 2	6 9	6 7		
		否	0 . 5 6	1 . 0	8 9	8 3	7 8	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 7	7 4	8 4	8 0	7 7	7 4	7 3		
				1 . 2 5	9 3	8 7	8 3	8 0	9 2	8 7	8 3	8 0	9 0	8 5	8 2	7 9	8 8	8 4	8 1	7 9	7 7		
下方投影面積		c m ²	1 . 5	9 6	9 1	8 7	8 4	9 4	9 0	8 6	8 3	9 2	8 8	8 5	8 3	9 0	8 7	8 4	8 2	8 0			
等価発光面積			c m ²	2 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 6	9 2	9 0	8 8	9 4	9 1	8 9	8 7	8 5		
取付	器具間隔最大限			2 . 5	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 8		
高さ	横方向 (A)		縦方向 (B)	3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0		
H m	0 . 4 3 H m		0 . 4 3 H m	4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 1	9 9	9 7	9 6	9 8	9 7	9 6	9 4	9 2		
				5 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 2	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4		
				7 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 3	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 6		
				1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 7			

