

屋内照明器具特性

品番 (品名)	L G W 8 5 0 5 7 Z														
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m														
管理番号	K0126479(0)DR1														
BZ分類	BZ9/0.7/BZ8														

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
		床	10 %				10 %				10 %				10 %				0 %		
上方光束	41 %	室指数																			
下方光束	42 %	照明率 (X0.01)																			
		ZCM																			
保守率	良 中 否	0.63	0.6	0.6	37	27	20	16	34	25	19	14	28	21	16	12	22	17	13	10	5
		0.6	0.8	4.4	3.4	2.7	2.2	4.0	3.1	2.5	2.0	3.3	2.6	2.1	1.7	2.6	2.1	1.7	1.4	8	
		0.56	1.0	4.9	3.9	3.2	2.7	4.5	3.6	3.0	2.5	3.7	3.0	2.5	2.1	2.9	2.4	2.0	1.7	10	
			1.25	5.3	4.4	3.7	3.2	4.9	4.1	3.4	3.0	4.0	3.4	2.9	2.5	3.2	2.7	2.4	2.0	13	
下方投影面積	c m ²	1.5	5.7	4.8	4.1	3.6	5.2	4.4	3.8	3.3	4.3	3.7	3.2	2.8	3.5	3.0	2.6	2.3	15		
		2.0	6.1	5.4	4.8	4.2	5.6	5.0	4.4	3.9	4.7	4.1	3.7	3.3	3.8	3.4	3.0	2.8	18		
		2.5	6.4	5.8	5.2	4.7	5.9	5.3	4.8	4.4	4.9	4.5	4.1	3.7	4.0	3.7	3.3	3.1	21		
取付高さ	器具間隔最大限		3.0	6.6	6.0	5.5	5.1	6.1	5.6	5.1	4.7	5.1	4.7	4.3	4.0	4.2	3.9	3.6	3.3	2.3	
	横方向 (A)	縦方向 (B)	4.0	6.9	6.4	6.0	5.6	6.4	6.0	5.6	5.2	5.4	5.0	4.7	4.4	4.4	4.2	3.9	3.7	2.5	
H m	1.51 H m	1.54 H m	5.0	7.1	6.7	6.3	5.9	6.6	6.2	5.9	5.5	5.6	5.3	5.0	4.7	4.6	4.3	4.1	3.9	2.7	
			7.0	7.3	7.0	6.7	6.4	6.8	6.5	6.2	6.0	5.8	5.5	5.3	5.1	4.8	4.6	4.4	4.3	3.0	
			10.0	7.5	7.3	7.0	6.8	7.0	6.8	6.5	6.3	5.9	5.8	5.6	5.4	5.0	4.8	4.7	4.5	3.3	

