

屋内照明器具特性	
品番 (品名)	LGW51784
光源	LED5000_70_1010 x1 1010.0 1m
管理番号	K0161585(0)DB1
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 14%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	86%	床		10%				10%				10%				10%				0%			
室指数			照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.3	4.0	3.2	2.7	5.1	3.9	3.1	2.6	4.7	3.7	3.0	2.5	4.3	3.5	2.9	2.4	2.1			
	中	0.6	0.8	6.2	5.0	4.2	3.6	6.0	4.9	4.1	3.5	5.5	4.6	3.9	3.4	5.1	4.3	3.7	3.3	2.9			
	否	0.56	1.0	6.8	5.7	4.9	4.3	6.6	5.5	4.8	4.2	6.1	5.2	4.6	4.1	5.7	4.9	4.3	3.9	3.5			
			1.25	7.4	6.4	5.6	5.0	7.1	6.2	5.5	4.9	6.6	5.8	5.2	4.7	6.2	5.5	5.0	4.5	4.1			
下方投影面積	c m <sup>2</sup>		1.5	7.8	6.9	6.1	5.5	7.6	6.7	6.0	5.4	7.0	6.3	5.7	5.2	6.5	5.9	5.4	5.0	4.5			
	等価発光面積		c m <sup>2</sup>	2.0	8.4	7.6	6.9	6.4	8.1	7.4	6.7	6.2	7.6	6.9	6.4	6.0	7.0	6.5	6.1	5.7	5.2		
取付高さ	器具間隔最大限		2.5	8.8	8.0	7.4	6.9	8.5	7.8	7.3	6.8	7.9	7.4	6.9	6.5	7.4	6.9	6.6	6.2	5.7			
	横方向 (A)	縦方向 (B)	3.0	9.0	8.4	7.8	7.4	8.7	8.1	7.6	7.2	8.2	7.7	7.3	6.9	7.6	7.2	6.9	6.6	6.0			
H m	1.31H m	1.31H m	4.0	9.4	8.8	8.4	8.0	9.1	8.6	8.2	7.8	8.5	8.1	7.8	7.4	8.0	7.7	7.4	7.1	6.5			
			5.0	9.6	9.1	8.7	8.4	9.3	8.9	8.5	8.2	8.7	8.4	8.1	7.8	8.2	7.9	7.7	7.4	6.8			
			7.0	9.8	9.5	9.2	8.9	9.5	9.2	8.9	8.7	9.0	8.7	8.5	8.3	8.4	8.2	8.0	7.9	7.2			
			10.0	10.0	9.7	9.5	9.3	9.7	9.5	9.3	9.1	9.2	9.0	8.8	8.6	8.7	8.5	8.4	8.2	7.6			

