

屋内照明器具特性	
品番 (品名)	L G D 3 2 0 4 V
光源	LED3500_70_735 ×1 735.0 l m
管理番号	K0153105 (0) D 1
B Z 分類	B Z 4 / 1 . 4 / B Z 3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	6 0	4 8	4 1	3 6	5 9	4 8	4 1	3 6	5 6	4 7	4 0	3 6	5 4	4 6	4 0	3 6	3 4				
			0 . 6 3	0 . 8	7 0	6 0	5 2	4 7	6 9	5 9	5 2	4 7	6 6	5 8	5 1	4 7	6 4	5 6	5 1	4 6	4 5				
			1 . 0	7 7	6 7	6 0	5 5	7 6	6 7	6 0	5 5	7 3	6 5	5 9	5 5	7 0	6 4	5 8	5 4	5 2					
			0 . 5 6	1 . 2 5	8 3	7 4	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 6	7 0	6 6	6 2	6 0				
下方投影面積 等価発光面積		c m ²	1 . 5	8 7	7 9	7 3	6 9	8 6	7 9	7 3	6 8	8 3	7 7	7 2	6 8	8 0	7 5	7 1	6 7	6 5					
			c m ²	2 . 0	9 2	8 6	8 1	7 7	9 1	8 5	8 1	7 7	8 8	8 3	7 9	7 6	8 6	8 2	7 8	7 5	7 3				
取付 高さ	器具間隔最大限		2 . 5	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 2	9 2	8 7	8 4	8 1	8 9	8 6	8 3	8 0	7 8					
	横方向 (A) 縦方向 (B)		3 . 0	9 8	9 3	9 0	8 6	9 6	9 2	8 9	8 6	9 4	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 1					
H m	1 . 2 0 H m	1 . 2 0 H m	4 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 5					
			5 . 0	1 0 2	9 9	9 7	9 4	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 8					
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 6	9 5	9 4	9 1					
			1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 0	9 9	9 8	9 9	9 8	9 7	9 7	9 4					

