

屋内照明器具特性	
品番 (品名)	L G D 3 4 0 0
光源	LED2700_70_595 ×1 595.0 l m
管理番号	K0154579 (0) DB 1
B Z 分類	B Z 3

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	6 3	5 2	4 5	4 0	6 1	5 1	4 4	4 0	5 9	5 0	4 4	4 0	5 7	4 9	4 4	3 9	3 8	
			0 . 6 3	0 . 8	7 3	6 3	5 6	5 2	7 2	6 2	5 6	5 1	6 9	6 1	5 5	5 1	6 7	6 0	5 5	5 1	4 9	
			0 . 5 6	1 . 0	8 0	7 1	6 4	6 0	7 8	7 0	6 4	5 9	7 6	6 9	6 3	5 9	7 3	6 7	6 3	5 9	5 7	
			1 . 2 5	8 5	7 7	7 2	6 7	8 4	7 7	7 1	6 7	8 1	7 5	7 0	6 6	7 9	7 4	6 9	6 6	6 4		
下方投影面積 等価発光面積		c m ²	1 . 5	8 9	8 2	7 7	7 2	8 8	8 1	7 6	7 2	8 5	7 9	7 5	7 1	8 2	7 8	7 4	7 1	6 9		
			2 . 0	9 4	8 8	8 3	8 0	9 2	8 7	8 3	7 9	9 0	8 5	8 2	7 8	8 7	8 4	8 0	7 8	7 5		
取付 高さ	器具間隔最大限		2 . 5	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	8 0		
	横方向 (A) 縦方向 (B)		3 . 0	9 9	9 4	9 1	8 8	9 7	9 3	9 0	8 7	9 5	9 1	8 9	8 6	9 2	9 0	8 7	8 5	8 3		
H m	1 . 2 1 H m	1 . 2 1 H m	4 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 2	9 0	9 5	9 3	9 1	8 9	8 7		
			5 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9		
			7 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2		
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 9	9 9	9 8	9 7	9 4		

