

屋内照明器具特性	
品番 (品名)	L G D 3 4 0 3 N
光源	LED5000_70_595 ×1 595.0 lm
管理番号	K0151662 (0) DB 1
BZ分類	BZ3 / 6.0 / BZ2

器具効率		1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
					室指数		照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	6 3	5 2	4 5	4 0	6 2	5 2	4 5	4 0	6 0	5 1	4 4	4 0	5 8	5 0	4 4	4 0	3 8		
			0 . 6 3	0 . 8	7 3	6 4	5 7	5 2	7 2	6 3	5 7	5 2	7 0	6 2	5 6	5 2	6 8	6 1	5 6	5 2	5 0		
			1 . 0	8 0	7 1	6 5	6 1	7 9	7 1	6 5	6 0	7 6	6 9	6 4	6 0	7 4	6 8	6 3	6 0	5 8			
			0 . 5 6	1 . 2 5	8 6	7 8	7 3	6 8	8 5	7 7	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 4	7 0	6 7	6 5		
下方投影面積		c m ²	1 . 5	9 0	8 3	7 8	7 3	8 8	8 2	7 7	7 3	8 6	8 0	7 6	7 3	8 3	7 9	7 5	7 2	7 0			
			等価発光面積		c m ²	2 . 0	9 4	8 9	8 5	8 1	9 3	8 8	8 4	8 0	9 1	8 6	8 3	8 0	8 8	8 5	8 1	7 9	7 7
取付高さ		器具間隔最大限		2 . 5	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1		
		横方向 (A)		縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	9 0	8 7	9 3	9 0	8 8	8 6	8 4
H m		1 . 2 0 H m		1 . 2 0 H m		4 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 3	9 1	9 5	9 3	9 2	9 0	8 8			
						5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 2	9 0
						7 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3
						1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5

