

屋内照明器具特性	
品番 (品名)	L G D 3 4 0 3 V
光源	LED3500_70_580 ×1 580.0 l m
管理番号	K0151662 (0) DB 1
B Z 分類	BZ3 / 6.0 / BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		1 0 0 %																						
保守率		良 中 否	0 . 6 7	0 . 6	6 3	5 2	4 5	4 0	6 2	5 2	4 5	4 0	6 0	5 1	4 4	4 0	5 8	5 0	4 4	4 0	3 8			
			0 . 6 3	0 . 8	7 3	6 4	5 7	5 2	7 2	6 3	5 7	5 2	7 0	6 2	5 6	5 2	6 8	6 1	5 6	5 2	5 0			
			0 . 5 6	1 . 0	8 0	7 1	6 5	6 1	7 9	7 1	6 5	6 0	7 6	6 9	6 4	6 0	7 4	6 8	6 3	6 0	5 8			
				1 . 2 5	8 6	7 8	7 3	6 8	8 5	7 7	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 4	7 0	6 7	6 5			
下方投影面積		c m ²	1 . 5	9 0	8 3	7 8	7 3	8 8	8 2	7 7	7 3	8 6	8 0	7 6	7 3	8 3	7 9	7 5	7 2	7 0				
等価発光面積			c m ²	2 . 0	9 4	8 9	8 5	8 1	9 3	8 8	8 4	8 0	9 1	8 6	8 3	8 0	8 8	8 5	8 1	7 9	7 7			
2 . 5	9 7			9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1					
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1				
	横方向 (A)		縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	9 0	8 7	9 3	9 0	8 8	8 6	8 4		
H m	1 . 2 0 H m		1 . 2 0 H m		4 . 0	1 0 1	9 8	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 3	9 2	9 0	8 8		
					5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 2	9 0		
					7 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3		
					1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		

