

# 屋内照明器具特性

品番 (品名)	L S E B 4 0 3 1									
光源	LED5000_70_453 ×1					453.0 l m				
管理番号	K0152279 ( 0 ) DB 1									
B Z 分類	B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		23 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		77 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X 0.01 )																			Z C M	
保守率	良	0.63	0.6	50	37	29	24	47	36	28	23	43	33	26	22	38	30	24	20	17	
	中	0.6	0.8	59	47	39	32	56	45	37	31	51	41	35	30	45	38	32	28	23	
	否	0.56	1.0	65	54	45	39	62	51	44	38	56	47	41	35	50	43	38	33	28	
			1.25	71	60	52	46	68	58	50	44	61	53	47	42	55	48	43	39	33	
下方投影面積	c m <sup>2</sup>		1.5	75	65	57	51	72	62	55	50	65	57	51	46	58	52	47	43	37	
	等価発光面積		c m <sup>2</sup>	2.0	81	72	65	59	77	69	63	57	70	64	58	54	63	58	54	50	43
取付高さ	器具間隔最大限		2.5	85	77	71	65	81	74	68	63	73	68	63	59	67	62	58	55	47	
	横方向 (A)	縦方向 (B)	3.0	87	80	75	69	83	77	72	67	76	71	66	63	69	65	61	58	51	
H m	1.41 H m	1.35 H m	4.0	91	85	80	76	87	82	77	73	79	75	71	68	72	69	66	63	55	
			5.0	93	88	84	80	89	85	81	77	81	78	75	72	74	72	69	67	58	
			7.0	95	92	88	85	91	88	85	82	84	81	79	76	77	75	73	71	62	
			10.0	97	95	92	90	94	91	89	86	86	84	82	80	79	78	76	74	66	

