

屋内照明器具特性

品番 (品名)	LSEB4029														
光源	LED3500_70_447 x1 447.0 lm														
管理番号	K0151935(0)DB1														
BZ分類	BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	28%																				
下方光束	72%																				
室指数	照明率 (X0.01) ZCM																				
保守率	良 0.63 中 0.6 否 0.56	0.6	49	36	28	23	46	35	27	22	41	31	25	20	36	28	23	19	15		
		0.8	58	46	38	32	55	44	36	30	49	40	33	28	43	36	30	26	21		
		1.0	64	53	44	38	61	50	43	37	54	45	39	34	48	41	35	31	26		
		1.25	70	59	51	45	66	56	49	43	59	51	45	40	52	46	41	37	30		
下方投影面積 等価発光面積	c m ²	1.5	74	64	57	50	70	61	54	48	63	55	49	45	56	50	45	41	34		
		2.0	80	71	64	58	76	68	62	56	68	61	56	52	60	55	51	47	40		
		2.5	84	76	70	64	79	72	67	62	71	66	61	57	64	59	55	52	44		
取付高さ	器具間隔最大限		3.0	86	79	74	69	82	76	71	66	74	69	64	61	66	62	59	55	47	
	横方向 (A)	縦方向 (B)																			
H m	1.46 H m	1.46 H m	4.0	90	84	79	75	85	80	76	72	77	73	69	66	69	66	63	60	51	
			5.0	92	87	83	79	87	83	79	76	79	76	73	70	71	68	66	64	54	
			7.0	94	91	87	84	90	87	84	81	82	79	77	74	74	72	70	68	58	
			10.0	96	94	91	89	92	90	87	85	84	82	80	78	76	74	73	71	61	

