

屋内照明器具特性	
品番 (品名)	L G D 5 2 2 2 V
光源	L E D 3 5 0 0 _ 7 0 _ 8 4 0 × 1 8 4 0 . 0 l m
管理番号	K 0 1 6 1 5 8 3 (1) D B 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	室指数	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良	0 . 6 7	0 . 6	8 9	8 4	8 1	7 9	8 8	8 4	8 1	7 9	8 7	8 3	8 1	7 9	8 6	8 3	8 0	7 8	7 8
		中	0 . 6 3	0 . 8	9 4	8 9	8 6	8 4	9 3	8 9	8 6	8 4	9 2	8 8	8 6	8 4	9 1	8 8	8 5	8 4	8 3
		否	0 . 5 6	1 . 0	9 7	9 3	9 0	8 8	9 6	9 2	9 0	8 8	9 4	9 1	8 9	8 7	9 3	9 1	8 9	8 7	8 6
				1 . 2 5	9 9	9 6	9 3	9 1	9 8	9 5	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	9 0	8 8
下方投影面積		c m ²		1 . 5	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 5	9 3	9 2	9 0
等価発光面積		c m ²		2 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 6	1 0 0	9 8	9 6	9 5	9 8	9 7	9 5	9 4	9 2
取付 高さ	器具間隔最大限			2 . 5	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 7	9 6	9 4
	横方向 (A)		縦方向 (B)	3 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7	9 5
H m	0 . 3 7 H m		0 . 3 7 H m	4 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	1 0 0	9 9	9 8	9 6
				5 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 0	9 9	9 7
				7 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 8
				1 0 . 0	1 0 7	1 0 7	1 0 6	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	9 8

