

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 3
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0175502 (0) DR 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	52	42	36	32	51	42	36	32	49	41	35	32	47	40	35	31	30
			0.63	0.8	61	52	46	42	59	51	46	41	57	50	45	41	55	49	45	41	39
			0.56	1.0	66	58	53	49	65	58	52	48	63	57	52	48	61	55	51	48	46
				1.25	71	64	59	55	70	64	59	55	68	62	58	54	66	61	57	54	52
下方投影面積 等価発光面積		cm ² cm ²		1.5	75	68	64	60	73	68	63	59	71	66	62	59	69	65	61	58	57
				2.0	79	74	70	66	78	73	69	66	75	71	68	65	73	70	67	65	63
				2.5	81	77	74	71	80	76	73	70	78	75	72	69	76	73	71	69	67
				3.0	83	80	76	74	82	79	76	73	80	77	74	72	78	75	73	71	69
H m	1.25 H m	1.25 H m		4.0	85	83	80	78	84	82	79	77	82	80	78	76	80	78	76	75	73
				5.0	87	84	82	80	86	83	81	80	83	82	80	78	81	80	78	77	75
				7.0	88	86	85	83	87	85	84	83	85	84	82	81	83	82	81	80	78
				10.0	89	88	87	86	88	87	86	85	86	85	84	83	84	83	83	82	80

